SUPERMARKET



supermarket - deli







	CGD1220SC	CGD1830SC	CGD2440SC
Height	1350mm	1350mm	1350mm
Width	1300mm	1910mm	2520mm
Depth	1100mm	1100mm	1100mm
Height (crated)	1590mm	1590mm	1590mm
Width (crated)	1420mm	2030mm	2650mm
Depth (crated)	1240mm	1240mm	1240mm
Weight – Nett	158kg	231kg	260kg
Weight – Crated	185kg	262kg	305kg
Display Area	0.78m2	1.37m2	1.73m2
Voltage	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz
Amperage	4A	4.6A	5.8A
Compressor Wattage	713watts	926watts	1285watts
Compressor Refrigerant	R134A	R134A	R134A
Cooling Fans	1	2	3
Temperature Range	4° to 8°C	4° to 8°C	4° to 8°C
Defrost Method	Forced	Forced	Forced

features

- Front sliding glass for easy cleaning
- Aesthetically pleasing aluminium sections used
- Removable colour coded plastic bumper rail insert
- Adjustable feet for leveling cabinet
- Chromadeck exterior finish
- Stainless steel work top for extra durability
- Polyurethane foam injection
- Temperature regulation by thermostat
- Automatic element burn out protection
- Light switch
- Top rear sliding doors



emd equipped™

Breakthrough technology replaces a conventional thermostat with an advanced electronic energy management system to cool quicker and maintain a more consistent temperature, while saving precious electricity.



green advantage™

By combining EMD control with ECM fans, electronic expansion valves and high-performance coils, we are able to further reduce energy consumption while improving cooling performance.



low e cabinet™

A superior combination of LED lighting, polyurethane insulation and low emissivity glass yields power savings around 40% lower than conventional refrigeration units.