SUPERMARKET



meat case - curved glass







	CGM1220SC	CGM1830SC	CGM2440SC
Height	1350mm	1350mm	1350mm
Width	1300mm	2010mm	2520mm
Depth	1100mm	1100mm	1100mm
Height (crated)	1450mm	1450mm	1450mm
Width (crated)	1340mm	2050mm	2570mm
Depth (crated)	1160mm	1160mm	1160mm
Weight – Nett	158kg	218kg	300kg
Weight – Crated	185kg	265kg	345kg
Display Area	0.78m2	1.37m2	1.728m2
Voltage	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz
Amperage	3.8A	4.6A	5.8A
Compressor Watts	584watts	989watts	1250watts
Compressor Refrigerant	R134A	R134A	R134A
Cooling Fans	1	2	3
Temperature Range	-2° to +2°C	-2° to +2°C	-2° to +2°C
Defrost Method	Electric	Electric	Electric

features

- Front sliding glass for easy cleaning
- Aesthetically pleasing aluminium sections used
- Removable colour coded plastic bumper rail insert
- Stainless Steel dishes supplied with unit
- Forced air cooling
- Adjustable feet for leveling cabinet
- Chromadeck exterior finish
- Stainless steel interior base
- Stainless steel worktop for extra durability
- Rear plug point for electronic scale etc
- Polyurethane foam injection
- Temperature regulation by thermostat
- Automatic defrost
- Light switch
- Top rear sliding doors



emd equipped™

Breakthrough technology replaces a conventional thermostat with an advanced electronic energy management system to cool quicker and maintain a more consistent temperature, while saving precious electricity.



green advantage™

By combining EMD control with ECM fans, electronic expansion valves and high-performance coils, we are able to further reduce energy consumption while improving cooling performance.



low e cabinet™

A superior combination of LED lighting, polyurethane insulation and low emissivity glass yields power savings around 40% lower than conventional refrigeration units.