QUB4PLTS/C

underbar - polar top



	QUB4PLTH	QUB6PLTH	QUB8PLTH
Doors	1.5	2.5	3.5
Height (with castors)	900mm	900mm	900mm
Width	1180mm	1780mm	2380mm
Depth	650mm/750mm	650mm/750mm	650mm/750mm
Weight	110Kgs	170Kgs	190Kgs
Temperature Range	2° to 6°C	2° to 6°C	2° to 6°C
Refrigerant	R290	R290	R290
Internal Volume (Litres)	200	450	700

features

- Stainless Steel grade 430 satin finish no 4 for sides, top and front grid
- Galvanized Steel Rear and Bottom

REFRIGERATION

- Polyurethane foam injection insulation
- Robust top and bottom hinges
- Fully adjustable heavy duty plastic coated shelves
- Digital temperature display with high/low voltage protection
- Self-closing doors

SABS

- Robust handles on doors
- All underbars supplied with brake castors
- Adjustable thermostat 2°C 6°C
- Auto Evaporation (The condensate is evaporated, hence no need to drain)

SARS

• All models are 220V – Plug in and switch on



emd equipped™

Breakthrough technology replaces a conventional thermostat with an advanced electronic energy management system to cool quicker and maintain a more consistent temperature, while saving precious electricity.



green advantage™

By combining EMD control with ECM fans, electronic expansion valves and high-performance coils, we are able to further reduce energy consumption while improving cooling performance.



swift swop™

Our innovative swift swop™ technology enables easy repalcement of the refrigeration deck without unpacking the contents of the fridge and without any skilled labour.



low e cabinet™

A superior combination of LED lighting, polyurethane insulation and low emissivity glass yields power savings around 40% lower than conventional refrigeration units.

•	
2	
•	
	H H
	••
2	
•	

